

LITHIO TECHNOLOGY ICE RESURFACER







SIMPLY SMART



Ice fields up to

1.800 m²



Blade width 2000 / 2.300 mm



Snow tank volume 3,0 m³ (compr. 3,6 m³)



Water tank volume

1.000 L

Technical data sheet

LITHIO TECHNOLOGY ICE RESURFACER





KEY FACTS

Technical specifications

ICE FIELDS	up to 1.800 m ²
DIMENSIONS L X W X H *	4.060 x 2.150 x 2.200 mm
HEIGHT WITH SNOW TANK UP	2.900 mm
HEIGHT INCLUDING DRIVER'S CABIN	2.550 mm
BLADE WIDTH	2000 / 2.300 mm
TURNING RADIUS	4.000 mm
GROUND CLEARANCE	195 mm
TRACK WIDTH	1.530 mm
WHEELBASE	1.975 mm
WATER TANK VOLUME	1.000 L
SNOW TANK VOLUME	3,0 m³ (compressed 3,6 m³)
EMPTY / WEIGHT STANDARD EQUIPMENT	3.638 kg (without extras)
WEIGHT / LOADED	4.638 kg

BATTERY	Battery / LITHIO technology 80 V / 240 Ah & battery charger
MOTOR	4 asynchronous motor
DRIVE SYSTEM	Electric all-wheel drive
CONVOYERS ENGINE	Electric motor
SPEED	max. 13 km/h
PUMP PRESSURE OF WORKING UNITS	160 bar
HYDRAULIC OIL TANK	70 L
TIRES	225 x R16" (studded tires)
WHEEL RIMS	8,0 x 16"



^{*} Length x width x height

LITHIO TECHNOLOGY ICE RESURFACER



KEY FACTS


Technical specifications
















Technical data sheet

LITHIO TECHNOLOGY ICE RESURFACER









STANDARD EQUIPMENT



SAFETY SYSTEMS

- · Quick-blade change system, developed by ENGO in 1997
- · Auger washout system, developed by ENGO in 2001
- · Safety switch for snow tank and conditioner
- EMERGENCY/OFF switch
- · Acoustic signal when reversing
- · Acoustic signal when operating snow tank
- · Acoustic signal when reversing auger
- · Servo-assisted oil bath brakes on all 4 wheels
- · Handbrake (negative brake)
- · Tow hook

ELECTRICAL SYSTEMS AND DRIVE

- DRIVE: direct electromechanical all-wheel axle drive with studded tyres
- · HYDRAULICS: direct electromechanical hydraulic pump drive
- MOTORS / AUGER MOTORS: Maintenance-free electric asynchronous motors

COCKPIT ENVIRONMENT

- · Access aids in accordance with CE directives
- · Suspended, adjustable driver 's seat with armrest
- · Foot pedals for acceleration and brake
- Steering wheel with power assistance
- Direction lever D/N/R
- 4.3-inch colour display with touch screen
- · Easy-to-operate hydraulic levers for work functions
- · CAN-BUS keypad for secondary functions
- USB interface
- · Lockable storage compartment
- Side mirrors (heated as an option)

CONTROL SYSTEMS

- LITHIO version: SmartConnect remote maintenance system (WLAN) for 1 year
- Automatic maintenance display
- CAN-BUS system
- · Ice boost system for augers
- · Digital battery level indicator

- · Digital display of the hydraulically adjustable cutting depth
- · Digital water level indicator
- · Sensor for water temperature

LIGHTING SYSTEMS

- · 4 LED front headlights and 2 rear lights
- · LED snow tank headlights
- · LED rotating beacon

HYDRAULIC SYSTEMS

- · Hydraulic cylinders for snow tank and conditioner
- · Hydraulic blade depth adjustment
- · Hvdraulically driven side brush
- · Hydraulic emergency hand pump

WATER SYSTEM

- · Water filling system with automatic filling stop
- · Manually adjustable water drain
- · Automatic water level shut-off valve
- · 2 wiping cloths

CONFIGURATION AND FILLING QUANTITY

- Steel snow tank with a capacity of 3.0 m³ (compressed 3.6 m³)
- Water tank in PE HD with a capacity of 1,000 litres
- Powder-coated, hot-dip galvanized conditioner with width of 2,000 mm

ACCESSORIES INCLUDED

- · Special tools for service and blade replacement
- 2 planer knives made of high-alloy steel with 45 - 60 operating hours
- 2 wiping cloths
- Various sets of spare parts
- Manual, including spare parts catalogue with USB stick (digital)



Technical data sheet

LITHIO TECHNOLOGY ICE RESURFACER





BATTERY EQUIPMENT 🗸 🕀 📖









LITHIUM BATTERIES AND CHARGERS

- Battery with LITHIO technology 80 V / 240 Ah
- Additional Lithium Power Pack of 120 Ah each up to max. 600 Ah

- Charger with AUTOMOTIVE charging plug
- · Various chargers available according to customer requirements for charging time and charging curve

OPTIONAL EQUIPMENT ①



COCKPIT ENVIRONMENT

- · Height-adjustable steering wheel
- · Heated cab with color glazing, DAB radio and stereo system
- · Driver 's seat with air suspension and seat heating
- Windscreen
- · Front and/or rear view camera

CONTROL AND MEASUREMENT SYSTEMS

- Extension of the SmartConnect remote maintenance system for 1.5 or 10 years
- · Parking sensors
- · Integrated laser beam as driving aid

LIGHTING SYSTEMS

- · LED work lights for side brushes
- · Underbody lighting (RGB colours)

WORKING SYSTEMS

- · Powder-coated, stainless steel conditioner with a planing width of 2,150 mm or 2,300 mm
- Scoring harrow for ice stock sport 2.000, 2.150 mm or 2.300mm with quick-release fasteners

WATER SYSTEMS

- · Automatic, speed-dependent water management
- Snow and water tank connection
- · IWS Ice washing system without high-pressure
- · WWS Tire washing system without high-pressure
- · TWS Tank washing system without high-pressure
- Solid Ice spraying system

CONFIGURATION AND FILLING QUANTITIES

- · Split water tank made of PE-HD with a volume of 1,000 litres (750/250) plus ON/OFF valve
- · Stainless steel water tank with 1.100 litres or 1.200 litres
- Stainless steel snow tank with 3.6 m³

VEHICLE SYSTEM

- · Studded spare wheel with rim
- Chrome rims

ACCESSORIES

- · Toolbox with quality tools





Engo GmbH | S.r.l.

Forchstraße | Via Forch 9 39040 Vahrn | Varna (BZ) · Italy T +39 0472 546 157

info@engo-ice.com www.engo-ice.com













ICE RESURFACER DASHER BOARDS ACCESSORIES

Powerful technology for smooth ice surfaces since 1979

CERTIFICATION













MEMBER OF THE TECHNOALPIN GROUP